

SHIPPING CONTAINERS

TERMS AND CONDITIONS

The terms and conditions for use of shipping containers placed on a local public road follow:

1. Shipping containers are considered as part of a Work Zone Application only. Note: Generally considered for building construction/ renovation sites to have temporary storage where required.
2. Documentation to be included with Work Zone application are a Traffic Control Plan, and Public Liability Insurance; a Statement of Purpose for the use of the container, and dimensions of the container must be provided including width, length and height (in metres).
3. Unless approved otherwise, placement of shipping containers on a road reserve/public place will only be permitted for a maximum of seven (7) days and only if the placement of such container is not possible within the applicant's site.
4. Unless approved otherwise, a shipping container must be on the public road carriageway and not on the footway.
5. The shipping container must be placed so there is at least 3 metres of the road alongside the container that is clear for other vehicles to pass. Note: a) The road must allow for designated on-road cycleways; and, b) Vehicles include service vehicles e.g. Waste collection trucks.
6. All shipping containers placed in a public place shall be marked so as to provide maximum safety to residents, pedestrians and other road users. E.g. flashing yellow lights and/or yellow reflective tape.
7. Any costs associated with damage caused to the road reserve by the delivery or placement of the container will be borne by the applicant.
8. Council reserves the right to require removal of the shipping container based on safety and or environmental grounds. Any removal of a container undertaken by Council will be borne by the applicant.

For further details refer to [Council's Work Zone application form](#).

Notes:

1. Any shipping container permitted on the footway must allow for safe pedestrian access.
2. If the shipping container is permitted for temporary placement on a footway, the shipping container must be at least 1.2m clear of any 150mm diameter sewer main or 2m clear of any 225mm (or greater) diameter sewer main; and, not be installed over drainage pipes or any house drainage pipelines unless access to the inspection openings is maintained at all times.

